



MODEL
28 KW/35 kVA
Stand-by Power @ 60 Hz

JM30U
25 kW / 32 kVA
Prime Power @ 60 Hz

Standard Features

- Engine (JOHN DEERE , 3029DF120)
- Charge alternator 12 V, Governor: Meca/Mechanical
- Alternator (MECC ALTE , ECO28VL)
- Single bearing alternator IP 23 , insulation class H /H
- Radiator 50°C [122°F]°C max. T°air inlet with cool ant cap
- Skid and vibration isolators
- Dry type air filter
- Microprocessor control panel
- Main line circuit breaker
- 12 V battery, rack and cable
- Industrial silencer (loose)
- User manual
CSA Certified (consult us)



Generator ratings

Voltage	HZ	Phase	PF	Stand by Amps	Stand by power kW/kVA	Prime power kW/kVA
480/277 V	60 Hz	3	0.8	42	28 / 35	25 / 32
440/254 V	60 Hz	3	0.8	46	28 / 35	25 / 32
240/120 V	60 Hz	3	0.8	84	28 / 35	25 / 32
230/115 V	60 Hz	3	0.8	83	26 / 33	24 / 30
220/127 V	60 Hz	3	0.8	92	28 / 35	25 / 32
208/120 V	60 Hz	3	0.8	97	28 / 35	25 / 32

Stand-By ratings are available for the duration of any power outage. No overload capacity is specified at this ratings. Prime ratings are available per BS 5514, DIN 6271, ISO-3046 and IEC 34-1 with 10% overload capacity one hour in twelve hours.

Conditions of sales

- SDMO provides a full line of products with high quality recognized engines and alternators.
- Service and parts are available from SDMO distributors as a single source of
- Each and every units is factory tested. All generator sets are also prototype tested.
- Two years limited warranty , please refer to the conditions terms . Five years extended are also available.

responsibility.



JM30U
specifications and design liable to modifications without prior notice

ENGINE DATA

Manufacturer / Model	3029DF120 , 4-cycle, Athmo , N/A
Cylinder Arrangement	3 X L
Displacement	2.9L [177.0C.I.]
Bore and Stroke	106mm [4.2in.] X 110mm [4.3in.]
Compression ratio	17,8 : 1
Rated RPM	1800 Rpm
Piston Speed	6.6m/s [21.7ft./s]
Max. stand by Power at rated RPM	34.1kW [46BHP]
Frequency regulation, steady state	+/-2, 5%
BMEP	7.1bar [103psij]
Governor : type	Meca/Mechanical

Exhaust System

Exhaust gas flow	102L/s [216cfm]
Exhaust temperature	570°C [1058°F]
Max back pressure	625mm CE [25in. WG]

Fuel System

110% (Stand By power)	9L/h [2.4gal/hr]
100% (of the Prime Power)	7.9L/h [2.1gal/hr]
75% (of the Prime Power)	6.3L/h [1.7gal/hr]
50% (of the Prime Power)	4.5L/h [1.2gal/hr]
Total fuel flow	108L/h [28.5gal/hr]

Oil System

Total oil capacity w/filters	6L [1.6gal]
Oil Pressure low idle	1bar [14.5psi]
Oil Pressure rated RPM	5bar [72.5psi]
Oil consumption 100% load	0.008L/h [0.0gal/hr]
Oil capacity carter	5.3L [1.4gal]

Thermal balance 100% load

Heat rejection to exhaust	31kW [1763Btu/mn]
Radiated heat to ambient	7kW [398Btu/mn]
Heat rejection to coolant	20kW [1137Btu/mn]

Air intake

Max. intake restriction	300mm CE [12in. WG]
Engine air flow	36L/s [76cfm]

Coolant System

Radiator & engine capacity	16.1L [4.3gal]
Max water temperature	105°C [221°F]
Outlet water temperature	93°C [199°F]
Fan power	2 kW
Fan air flow	2.22m ³ /s [4704cfm]
Available restriction on air flow	20mm CE [0.8in. WG]
Type of coolant	Gencool
Thermostat	82-94 °C

Emissions

HC	N/A
CO	N/A
Nox	N/A
PM	N/A



ALTERNATOR SPECIFICATIONS

GENERAL DATA

- Compliance with NEMA MG21, UTE NF C51.111, VDE 0530, BS 4999, CSA standards.
- Vacuum-impregnated windings with epoxy varnish.
- IP21 drip proof.

ALTERNATOR DATA

Manufacturer / Type	MECC ALTE ECO28VL
Number of phase	3
Power factor (Cos Phi)	0.8
Altitude	1000
Overspeed	rpm
Pole : number	4
Exciter type	No
Insulation : class, temperature rise	H / H
Voltage regulator	SR7/2
Sustained short circuit current	
Total harmonics (TGH/THC)	
Wave form : NEMA = TIF – TGH/THC	
Wave form : CEI = FHT – TGH/THC	
Bearing : number	1
Coupling	Direct
Voltage regulation 0 to 100% load	
Recovery time (20% Volt dip) ms	ms
SkVA with 90 % of nominal sustained voltage (at 0.4 PF)	N/A

OTHER ALTERNATOR DATA

Continuous nominal rating @ 40°C	36 kVA
Standby rating @ 27°C	36.3 kVA
Efficiencies @ 4/4 load	86.5 %
Air flow	5.8m ³ /s [12289.45cfm]
Short circuit ratio (Kcc)	0.62
Direct axis synchro reactance unsaturated (Xd)	165 %
Quadra axis synchro reactance unsaturated (Xq)	71 %
Open circuit time constant (T'do)	0.93 ms
Direct axis transient reactance saturated (X'd)	15.4 %
Short circuit transient time constant (T'd)	46 ms
Direct axis subtransient reactance saturated (X''d)	8.8 %
Subtransient time constant (T''d)	12 ms
Quadra axis subtransient reactance saturated (X''q)	19 %
Zero sequence reactance unsaturated (Xo)	2.8 %
Negative sequence reactance saturated (X2)	13.2 %
Armature time constant (Ta)	11 ms
No load excitation current (io)	A
Full load excitation current (ic)	A
Full load excitation voltage (uc)	V
Recovery time (Delta U = 20% transitoire)	ms
Motor start (Delta = 20% perm. Or 50% trans.)	kVA
Transient dip (4/4 charge) – PF : 1.8 AR	%
No load losses	kW
Heat rejection	kW



Control Panels

Standard panel : NEXYS



Specifications :

Frequency meter, Ammeter, Voltmeter

Alarms and faults Oil pressure, water temperature, Overcrank, Overspeed, Min/max alternator, Low fuel level, Emergency stop

Engine parameters :

Hours counter, Engine speed, Battery voltage, Fuel level, Air preheating

Optional panel : TELYS



Specifications :

Frequency meter, Ammeter, Voltmeter

Alarms and faults :

Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop

Engine parameters :

Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level



JM30U
specifications and design liable to modifications without prior notice

Options

<p>Engine and Radiator</p> <ul style="list-style-type: none"> ▪ Heat shield protection ▪ Oil drain extension ▪ Heavy duty air filter ▪ Lube oil drain pump ▪ Radiator core guard ▪ Battery charger ▪ Block heater 	<p>Alternator</p> <ul style="list-style-type: none"> ▪ Anti condensation heater ▪ Enforced impregnation ▪ Oversized alternator <p>Exhaust</p> <ul style="list-style-type: none"> ▪ Residential silencer ▪ Critical silencer ▪ Flexible exhaust conn. 	<p>Control panel</p> <ul style="list-style-type: none"> ▪ NFPA 110 level 1 ▪ Paralleling system ▪ Remote annunciator ▪ Oil temperature shutdown ▪ Key start panel
<p>Fuel</p> <ul style="list-style-type: none"> ▪ Day tank ▪ Subbase fuel tanks UL ▪ Water separator fuel filter 	<p>Enclosure M107</p> <ul style="list-style-type: none"> ▪ Silent 73 db @ 23 Ft (stby) 	<p>Literature</p> <ul style="list-style-type: none"> ▪ Parts ▪ Maintenance

Weight and Dimensions

Open Model



Overall size l x w x h :
1480mm [58in] x 780mm [31in] x 1180mm [46in]


Weight :
710kg [1565lbs] Net 820kg [1807lbs] Brut

With Optional Enclosure



Overall size l x w x h :
2100mm [83in] x 920mm [36in] x 1445mm [57in]

Weight :
1035kg [2281lbs] Net 1145kg [2524lbs] Brut



SDMO industries - Head Office – 12bis, rue de la Villeneuve – CS 92848 - 29228 BREST cedex 2 -
FRANCE www.sdmo.com



JM30U
specifications and design liable to modifications without prior notice